

DESIGN

- HEAVY DUTY MACHINED ALUMINIUM PROFILE
- BACKLASH FREE RACK AND PINION DRIVES
- GROUND LINEAR GUIDE
- NO LUBRICATION REQUIRED
- HEATING PROTECTION
- AIR COOLING READY

TECHNOLOGY

- PLASMA CUTTING
- OXY FUEL CUTTING
- MARKING

CONTROL

- INDUSTRIAL CNC CONTROL SYSTEM
- 15" COLOUR TOUCH SCREEN
- DIGITAL CONTROLLED AC SERVO SYSTEM
- INBUILT GAS CUTTING TECHNOLOGY
- INBUILT PLASMA CUTTING TECHNOLOGY

EQUIPMENT

- TOUCH SCREEN CONTROLLER
- GAS AND PLASMA QUICK CHANGE SUPPORT
- PLASMA TORCH INITIAL HEIGHT SENSING
- PLASMA TORCH HEIGHT CONTROL
- GAS HI-LOW MATERIAL PREHEATING
- GAS AUTOMATIC MATERIAL PERCING
- ANTICOLLISION SENSOR
- LASER POINTER



DIMENSIONS

| | WILDCAT 1500 | WILDCAT 2000 |
|----------------|--------------|--------------|
| CUTTING WIDTH | 1500 | 2000 |
| CUTTING LENGTH | 3000 - 6000 | 3000 - 6000 |
| MACHINE WIDTH | 2450 | 2900 |
| MACHINE LENGTH | 560 | 600 |
| MACHINE HEIGHT | 1500 | 1500 |
| MACHINE WEIGHT | 350 | 380 |

TECHNICAL DATA

| | |
|----------------------------------|-----------------------|
| MAX TRAVEL SPEED | 20 000 mm/min |
| MAX CUTTING THICKNESS - OXY FUEL | 100 mm |
| MAX CUTTING THICKNESS - PLASMA | ACCORDING PLASMA UNIT |
| | |
| STANDARD POWER SUPPLY | 230V /50 Hz |